

Product Information

Double-sided mounting tape based on an UV-cross-linked, closed-cell and durable elastic polyethylene foam coated with a solvent acrylic adhesive on both sides.

POLI-MOUNT 3705 offers very good ageing, UV and weathering stability and guarantees a high initial tack on structured and rough surfaces (concrete, structural varnish).

Composite materials with extremely different expansion rates can be mounted without tension.

POLI-MOUNT 3705 is suitable for the following applications:

- Mounting of hooks, holders, consoles, name plates and promotional boards.
- Mounting of mirrors, coverplates, cable trunking and electronic components.
- Self-adhesive mounting of displays and product samples.
- Mounting of objects at exhibitions and shop displays.

Technical Data

| | |
|-------------------------------------|---|
| Carrier: | PE-foam, white |
| Adhesive: | Solvent acrylic |
| Liner: | PE-paper, white (120 g/m ²) |
| Adhesion [N/cm]: | 5,80 +/- 10 % |
| Thickness [mm]: | 1,00 +/- 5 % |
| Temperature resistance [°C]: | -40 / +70 |

Standard Dimensions

1.240 mm x 50 m

Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.