

POLI-FIX 320

Product Information

POLI-FIX 320 is a double-sided tape with a fleece as carrier.

The acrylic adhesive offers a good ageing, UV and temperature resistance.

Due to the high initial tack POLI-FIX 320 offers a good specific adhesion on nearly all materials.

Especially to be emphasised are the following properties:

- Mounting of displays and cover plates.
- · Self-adhesive finishing of polyester, polyether, PVC and polyethylene foams.
- · Laminating of roll material such as felt, film and tissue.
- · Splicing of paper and films.

Technical Data

Carrier: Fleece

Adhesive: Acrylic, modified

Silicone-paper, yellow (95 g/m²) Liner:

Adhesion [N/cm]: 6,00 +/- 10 %

Thickness [mm]: 0.10 +/- 5 %

Temperature

-40 / +120 resistance [°C]:

Standard Dimensions

1.500 mm x 100 m

1.500 mm x 50 m

Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

POLI-TAPE Klebefolien GmbH

Zeppelinstraße 17

Phone:

53424 Remagen - GERMANY

+49 (0) 2642 - 9836 0 +49 (0) 2642 - 9836 37 Fax: E-Mail: info@poli-tape.de Internet: www.poli-tape.de

28/07/2011

The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material.