

PROFIT ULTRA CLEAR GLOSS LAM

Technical Data Sheet



SPECIFICATION	DESCRIPTION	VALUE
PVC	Type	Calendered monomeric soft PVC film
	Thickness	80 ± 10 um
	Color Code	Ultra Clear
	Shrinkage	≤ 0,8 %
ADHESIVE	Type	Ultra clear solvent based permanent pressure sensitive adhesive
	Weight (g/m ²)	25 ± 2
	Adhesion temperature	15–40 °C
	180° peeling force	≥ 8N/25mm 20 min (GB2792-81 China National Standard)
	Initial Adhesion-ball tack	≥ 5# Steel ball (GB4852-84 China National Standard)
	Holding power	≥ 800 min (GB4854-84 China National Standard)
LINER	Type	PET liner
	Color	White
	Weight	75 ± 5 g/m ²
	Release Force	0,1–0,3 N/25 mm
STORAGE PERIOD	12 months under ordinary condition at temperature of 22 °C and relative humidity of 50–55 %	
APPLICATION	Outdoor digital and silk screen printing media for signage display, vehicle graphics, airport and subway graphics application.	
ACOMPATIBILITY OF MACHINES AND INK	Apply lamination film only after sufficient drying time of the ink! Surface and working space must be clean, to avoid dust and particles under the film! The best temperature to apply is 35–40 °C .	

Warranty and Limitation

These products are manufactured with high quality raw materials and advanced technology & equipment, guaranteed by serious and scientific quality control systems. All products are warranted to be free of defects in materials and manufacture at the time of shipment and to meet the product specification. Should there is any product defects caused by manufacturer, compensation will be limited within certain product price.

Data above are updated results and conclusions of test by the manufacturer and is subject to change without prior notice.

The supplier is not responsible for all the performance of this material for a given application. The users of materials should perform their own testing to determine the suitability of the material for the intended use.