

DirectTex® Softimage 240®

Fields of application

.02 .04 .05 .07

Specifications



599250 129



100 % polyester
knit fabrics
PVC-free, recyclable



ca. 160/ 252/ 320/ 505 cm
ca. 63/ 99/ 126/ 199 inch
other widths available on request



B-s1, d0 DIN EN 13501-1
M1 NF P 92 503 - 507



ca. 240 g/m²
ca. 7.08 oz/yd²



ca. 0.49 mm
ca. 490 µm



rolls
50/ 100 m
55/ 109 yd



length: 644.5 N
cross: 1223.9 N
DIN EN ISO 13934-1



length: 61.8 %
cross: 57.4 %
DIN EN ISO 13934-1



length: 1.6 %
cross: 0.9 %
DIN EN 14704-1



cold, ultrasonic cut

Printing methods

print	UV	Latex	Dyesub
Inside	•		•
Outside			

Article shrinkage (50 sec hold up time)

	shrinkage in cross direction	shrinkage in longitudinal direction	recommended fixing temperature
180°C	0,5 %	1,2 %	
190°C	/ %	/ %	
200°C	/ %	/ %	•
210°C	0,5 %	2,5 %	

Certifications



DirectTex® Softimage 240

Fields of application

.02 .04 .05 .07



Ref.-Nr.: 599250 129 | Preview print sample