

CLEAR FOCUS Imaging, Inc.

One Way Vision Window Graphics

CLEAR FOCUS™ ImageVue 1540 ONE WAY VISION™ FILM

Black/white composite, flexible PVC with removable acrylic pressure-sensitive adhesive and a solid release liner, perforated with 1.5 mm holes (approximately 40% open area), wound on 76mm cores.

Recommended for windows, glass doors and other transparent surfaces.

Makeup	Black/white PVC laminate with pressure-sensitive adhesive coating with release liner
Vinyl thickness	178 micron
Release liner thickness	170 micron
Adhesive thickness	20 micron
Standard widths	1.370 mm
Dimensional stability	Good
Minimum application temperature	+4°C
Service temperature range	-17°C to 62°C
Expected lifetime	2 to 3 years. 6 months for a clean removal. Adhesion may increase with time.
Water resistance	Immersion in water not recommended
Humidity resistance	Fair
Solvent resistance	Good
Storage stability	One-year shelf life when stored at 21 °C and 50% relative humidity.
Printing	Standard vinyl inks recommended. Print image on white (non-adhesive) side of the product, not on release sheet
Application	Apply to dry, clean glass surface. Use plain soap and water, rinse and dry the glass well. Do not use ammonia or other solvent-based glass cleaners prior to application
Removal	Remove by peeling from surface. Remove adhesive residue on older installations, if necessary

Clear Focus Germany

Hans-Michael Gerischer, Im Kaisergewann 26; 68239 Mannheim
PH: +49 (0) 171 771 5532 FX: +49 (0) 621 437 83 35 E-Mail: clearfocus@t-online.de

Headoffice: CLEAR FOCUS Imaging, Inc.

60 Maxwell Court, Santa Rosa, CA 95401 USA
PH: (707) 544-7990 FX: (707) 544-1886 E-mail: headoffice@clearfocus.com Web: www.clearfocus.com